HPPT0050001-00B
Date 2024-10-30
CN
EN Instruction Sheet

Suppo r ed Models

V304E V307S V307E V310S V310E V315E V315E-4G V315E-WIFI
V300-4G-ADP V300-WIFI-ADP

⚠

/

The products involved are all open-type housing designs. Therefore they should be installed in a control cabinet that is free of airborne dust, humidity, electric shock, and vibration. The cabinet should prevent non-maintenance sta f from operating the products or accidents from happening in case danger and damage may occur on the products.

V300
Please refer to the V300 series hardware manual for more detailed information.

V304E	2.4	2.4	DC24V DC19.2~28.8V	DC24V, voltage range: DC19.2~28.8V
V307S	4.8	4.8		
V307E	4.8	4.8		
V310S	7.2	7.2		
V310E	7.2	7.2		
V315E	14.4	14.4		
V315E-4G	14.4	14.4		
V315E-WIFI	14.4	14.4		
V300-4G-ADP	—	—		Powered by HMI
V300-WIFI-ADP	—	—		

*

*Note: All models are featured by the SELV input type.

	Altitude	≤2000m	≤2000m
	Operating environment		Installation within a control cabinet, open-type and indoor use
	Operating temperature	-0~55℃	-0~55℃
	Storage temperature	-20~60	-20~60
	Ambient humidity	10~95%RH	10~95%RH (non-condensation)
	Vibration resistance	5~150Hz X/Y/Z 1g/3.5mm	5~150Hz (X/Y/Z direction, 1g /3.5mm displacement)
	Pollution degree		Level 2
	Cooling method		Natural air cooling
	IP rating	IP65 IP20	Front panel: IP65, Back housing: IP20
	Enclosure material		Self-extinguishable

*

*Note: The equipment may be damaged if used in a manner not specifed by the manufacturer.

CN 0.5~0.7N.m	②嵌入人机界面 Embed the HMI into the	

CN	沿箭头方向插入端	


W4
H4
开孔尺寸
Hole dimension
H1
H2
W3
H3
D1
D2
D3
W2
139.00
7.53
42.2
55.00
642 approx.
201.00


4G-S
4G-PWR
WIFI-PWR

* 1 V304E V V315E-WIFI

*Note1: This inte r ac d on V304E, V315E, V315E-4G, and V315E-WIFI models.

* 2 V307S V 310E

*Note 2: This inte r a r ed on V307S, V307E, V310S, and V310E models.

串口通讯