⚠

/

personnel. Failure to do so may lead to serious risks to personnel safety and potential loss of prope r y.

M

Please refer to the M series hardware manual for more detailed information.

	Hechuan Technology)

MXB	M M-Series optional expansion

MA03	2AD+1DA (Analog 2AD+1DA)

200	M200 M200 series optional card

BD	BD Optional BD card)

XXXX	0~9/A~Z/ (N/A)

expansion card	HCMXB-MA03-200-BD	HCM211-20MR-A HCM211-20MT4-A HCM211-32MR-A HCM211-32MT6-A HCM211-42MR-A HCM211-42MT8-A HCM211-60MR-A HCM211-60MT10-A HCM212-32MT4-A HCM212-60MT8-A	2 1	

	≤2000m		≤ 2000m	
Operating environment				
Operating temperature	0~55		0~55	
Storage temperature	-25~70		-25~70	
	10~95%RH		10~95%RH (non-condensing)	
Vibration resistance	5~150Hz X/Y/Z	1g/3.5mm	5~150Hz (X/Y/Z direction, 1g /3.5mm displacement)	
	2		Level 2	
			Natural air cooling	
	IP20		IP20	
Enclosure material			Self-extinguishable	

*

*Note: If the equipment is used in a manner not speci f ed by the manufacturer, the protection provided by the equipment may be impaired.

CN



1+ channel 1+)	IN	VI1+